

### TYPICAL APPLICATION



Automotive



Com. Vehicle



Construction



Electrical



Energy



Industrial



Mass Transport



Sanitary

### PRODUCT DESCRIPTION

menzolit® HPC 1300 is a sheet moulding compound based on unsaturated polyester resin. The product is glass fibre reinforced and contains mineral fillers. In case of fire the product doesn't melt, neither does it form droplets nor is smoke generation excessive. The material is compression moulded in heated steel moulds. It is recommended to work with chrome plated tools. The product contains no halogens or heavy metals nor any candidates from the REACH SVHC list.

### PRODUCT SPECIFICATION

High strength material with unidirectional reinforcement. Especially high strength in fibre direction, high glass content.

### TYPICAL PROPERTIES

	Standard	Units	
Density	ISO 1183	g/cm <sup>3</sup>	1,7
Shrinkage	ISO 2577	%	0,2 / -0,05
Heat Distortion Temp.	EN ISO 75-2	°C	>200
Continuous Service Temp.	Menzolit	°C	170
Young's Modulus	EN ISO 527-4	GPa	12 / 25
Tensile Strength	EN ISO 527-4	MPa	70 / 410
Flexural Strength	EN ISO 14125	MPa	95 / 740
Flex Modulus	EN ISO 14125	GPa	11 / 28
Impact Strength	EN ISO 179	kJ/m <sup>2</sup>	40 / 370
Glow Wire Index	IEC 60707-3	°C	
Fire Retardancy	UL 94		
Surface Resistivity	IEC 60093	Ohm	10 <sup>12</sup>
Comparative Tracking Index	IEC 60112	Level	CTI600
Water Absorption	ISO 62	%	< 0,5

### FORM of SUPPLY

menzolit® HPC 1300 is produced in a standard width of 1500 mm. It is supplied on rolls holding up to 1500 kg. In any case a styrene barrier film wrapping is being used. For alternative packaging please contact our technical service team. Available in limited colours.